

MAHLE Behr Europe KLT Pool System

Table of contents

1. General processing of MAHLE Behr KLT-Pool System	2
1.1. Order process	2
1.2. RP account statement	2
1.3. Physical inventory	3
2. RP at MAHLE Behr KLT-Pool System	4
2.1. Overview 1 RP at MAHLE Behr Pool.....	4
2.2. Overview 2 RP at MAHLE Behr Pool.....	5
2.3. Overview 3 RP at MAHLE Behr Pool.....	6
2.4. Overview 4 RP at MAHLE Behr Pool.....	7
3. Implementation of MAHLE Behr Pool System at suppliers	8
3.1. Step1 - Identification of parts	8
3.2. Step2 - Access to the system	8
4. Logistics processing of MAHLE Behr Pool.....	9
4.1. Scheduling/delivery of RP	9
4.2. Cleanliness.....	10
4.3. Labeling (according VDA4902, VDA4994).....	10
4.3.1. System conform labeling:	11
4.3.2. System non-conform labeling:	12
4.4. Palletizing.....	13
4.5. Load securing.....	13
4.6. Goods receipt inspection process.....	14
4.7. Area of application for RP.....	14
4.8. Ergonomics	14
5. Contact person for logistic/technical standards.....	14

1. General processing of MAHLE Behr KLT-Pool System

1.1. Order process

The returnable packaging (RP) in this system may only be used for deliveries from the supplier to MAHLE Behr, from MAHLE Behr to the supplier, and for MAHLE Behr's internal deliveries. This applies to all deliveries to MAHLE Behr Group companies within Europe.

In addition, global and regional logistic guidelines must be considered.

Areas of application:

MAHLE Behr supplies the following European countries delivered duty unpaid and untaxed:

Austria, Belgium, Bulgaria, Czech Republic, Denmark, France Germany, Hungary, Italy, Luxembourg, Monaco, Netherlands, Poland, Romania, Serbia, Slovakia, Slovenia, Spain, and Switzerland.

Remaining countries of Europe:

In the remaining countries additional freight charges are calculated individually and charged to the buyer. Customs documents for export registration are prepared by MAHLE Behr and attached to the shipment. Resulting payments of duty and taxes including additional expenses will be charged to the consignee.

The supplier orders at MAHLE Behr the RP, required for his demands. The RP may only be used for deliveries to MAHLE Behr subsidiaries. The use for deliveries to other partners or pre-production is expressly prohibited.

MAHLE Behr supplies the RP to the supplier within the defined lead-time after receipt of order by e-mail.

1.2. RP account statement

For all RP a packaging-account must be implemented between supplier and MAHLE Behr. MAHLE Behr forwards its packaging account statement via e-mail monthly to supplier. Supplier must check accounts within permitted time period. In case of claims, supplier must add corresponding paperwork.

Packaging accounts for shared RP are managed by container-eu@mahle.com, only.

1.3. Physical inventory

Stock taking of all RP must be done minimum once per year. Date of stock taking is defined as 31.12.20xx.

Reports of stock taking must be returned at the defined date the latest.


In case of discrepancies from RP account to physical counting, reported stock will be overtaken into RP account.

Discrepancies that could not be clarified until the defined date will be charged to supplier with costs for replacement.

If no stock taking report is returned until defined date, RP account will be booked to "0" and booked quantity will be charged to exchange partner with costs for replacement.

2. RP at MAHLE Behr KLT-Pool System

2.1. Overview 1 RP at MAHLE Behr Pool

Packaging name: MU3			
Packaging number: BT05815			
Color: blue - RAL5005			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	800 mm	700 mm	
Width	400 mm	330 mm	
Height	323 mm	308 mm	
Weight	4,48 kg		
Superimposed load: 150 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1274 mm	140,96 kg	3	9

Packaging name: MU4			
Packaging number: BT00380			
Color: blue - RAL5005			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	600 mm	531 mm	
Width	400 mm	341 mm	
Height	330 mm	316 mm	
Weight	3,40 kg		
Superimposed load: 120 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1230 mm	156,00 kg	4	10

Packaging name: MU5			
Packaging number: BT00013			
Color: blue - RAL5005			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	600 mm	542 mm	
Width	400 mm	352 mm	
Height	218 mm	208 mm	
Weight	2,80 kg		
Superimposed load: 120 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1257 mm	165,60 kg	4	13



Packaging name: MU5L			
Packaging number: BT03073			
Color: ESD black Resistance: 10 ⁶ ohm			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	600 mm	542 mm	
Width	400 mm	352 mm	
Height	218 mm	214 mm	
Weight	3,05 kg		
Superimposed load: 120 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1257 mm	178,60 kg	4	13

2.2. Overview 2 RP at MAHLE Behr Pool



Packaging name: MU6			
Packaging number: BT00379			
Color: blue - RAL5005			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	400 mm	352 mm	
Width	300 mm	242 mm	
Height	218 mm	208 mm	
Weight	1,40 kg		
Superimposed load: 120 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1257 mm	165,60 kg	8	13

Packaging name: MU6L			
Packaging number: BT05138			
Color: ESD black Resistance: 10 ⁶ ohm			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	400 mm	352 mm	
Width	300 mm	242 mm	
Height	218 mm	214 mm	
Weight	1,60 kg		
Superimposed load: 120 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1257 mm	186,40 kg	8	13

Packaging name: MU7			
Packaging number: BT06501			
Color: blue - RAL5005			
			
Packaging details			
	EXTERNAL	INTERNAL	
Length	300 mm	238 mm	
Width	200 mm	150 mm	
Height	154 mm	143 mm	
Weight	0,55 kg		
Superimposed load: 95 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
685 mm	108,00 kg	16	10


Packaging name: MAHLE KLT4213			Lid name: LID D45
Packaging number: BT59936			Lid number: BT60297
Color: blue - RAL5005			
			
Packaging details			Lid details
	EXTERNAL	INTERNAL	
Length	400 mm	345 mm	400 mm
Width	300 mm	260 mm	300 mm
Height	213 mm	185 mm	-
Weight	1,42 kg		0,25 kg
Superimposed load: 600 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1265 mm	92,90 kg	8	5

2.3. Overview 3 RP at MAHLE Behr Pool



Packaging name: MAHLE KLT3147		Lid name: LID D35	
Packaging number: BT60471		Lid number: BT60296	
Color: blue - RAL5005			
			
Packaging details			Lid details
	EXTERNAL	INTERNAL	
Length	300 mm	243 mm	300 mm
Width	200 mm	162 mm	200 mm
Height	147 mm	130 mm	-
Weight	0,57 kg		0,09 kg
Superimposed load: 400 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1229 mm	100,02 kg	16	7


Packaging name: MAHLE KLT6147		Lid name: LID D65	
Packaging number: BT62593		Lid number: BT62539	
Color: blue - RAL5005			
			
Packaging details			Lid details
	EXTERNAL	INTERNAL	
Length	600 mm	544 mm	600 mm
Width	400 mm	359 mm	400 mm
Height	147 mm	130 mm	-
Weight	1,82 kg		0,52 kg
Superimposed load: 400 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1229 mm	91,62 kg	4	7


Packaging name: MAHLE KLT8420			
Packaging number: BT57600			
Color: grey			
			
Packaging details			
	EXTERNAL		INTERNAL
Length	800 mm		238 mm
Width	400 mm		238 mm
Height	200 mm		238 mm
Weight	2,93 kg		
Superimposed load: 380 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1200 mm	70,05 kg	3	5


Packaging name: LID A1208			
Packaging number: BT00233			
Color: blue - RAL5012			
			
Packaging details			
Length	1205 mm		
Width	805 mm		
Height	94 mm		
Weight	6,10 kg		
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1540 mm	172,50 kg	1	25

2.4. Overview 4 RP at MAHLE Behr Pool

Packaging name: MAHLE KLT4013		Lid name: LID D41	
Packaging number: BT63447		Lid number: BT63448	
Color: ESD black			
			
Packaging details			Lid details
	EXTERNAL	INTERNAL	
Length	400 mm	345 mm	400 mm
Width	300 mm	260 mm	300 mm
Height	213 mm	185 mm	-
Weight	1,54 kg		0,29 kg
Superimposed load: 400 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1265 mm	99,30 kg	8	5

Packaging name: MAHLE KLT6013		Lid name: LID D61	
Packaging number: BT63449		Lid number: BT63450	
Color: ESD black			
			
Packaging details			Lid details
	EXTERNAL	INTERNAL	
Length	600 mm	544 mm	600 mm
Width	400 mm	359 mm	400 mm
Height	213 mm	185 mm	-
Weight	2,54 kg		0,75 kg
Superimposed load: 400 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1265 mm	91,80 kg	4	5

Packaging name: EURO GIBO			
Packaging number: 804040			
Color: grey			
			
Packaging details			
Length	1235 mm		
Width	840 mm		
Height	970 mm		
Weight	70,00 kg		
Superimposed load: 5000 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
1890 mm	140,00 kg	1	2

Packaging name: EUROPALLET			
Packaging number: 804562			
Color: wood			
			
Packaging details			
Length	1200 mm		
Width	800 mm		
Height	144 mm		
Weight	20,00 kg		
Superimposed load: 6000 kg			
Handling unit stacking details for empty boxes			
Stack height	Weight	Per layer	Max layers
2304 mm	320,00 kg	1	16

3. Implementation of MAHLE Behr Pool System at suppliers

3.1. Step1 - Identification of parts

Based on the packaging specifications of MAHLE Behr, supplier defines the quantity of parts per packaging and adjusts these in consultation with the responsible Logistics team leader (Logistic Datasheet).

3.2. Step2 - Access to the system

Registration with Logistics MAHLE Behr Group: kltpool@mahle.com

Supplier receives additional information and the order form.

Address:

MAHLE Behr GmbH & Co KG
KLT-Pool Management / CITE
Pragstr. 26 - 46
D-70376 Stuttgart
Tel: +49 711 501 10225
E-mail: kltpool@mahle.com

4. Logistics processing of MAHLE Behr Pool

4.1. Scheduling/delivery of RP

Supplier is responsible for planning and scheduling the demand for RP. Supplier's order is sent by e-mail. Within a maximum of 7 working days after receipt of the order, delivery will be carried out by MAHLE Behr.

Lead time max. 7 working days:

Austria, Belgium, Bulgaria, Czech Republic, Denmark, France, Germany, Hungary, Italy, Luxembourg, Monaco, Netherlands, Poland, Romania, Serbia, Slovakia, Slovenia, Spain and Switzerland.

Shipments to other European countries will take place after previous coordination.

Shipment of empty RP takes place sorted and with defined package sizes. KLT 3147, 4013, 4213, 6013, 6147 and 8420 are to be stacked with the corresponding lid. Load securing for KLT and lids must be done with lid A1208 and plastic straps.

Euro pallet	(804562)	=	16	pcs. per stack
Euro Gibo	(804040)	=	2	pcs. per stack
1 pallet KLT3147	(BT60471)	=	112	pcs. (incl. lids D35 - BT60296)
1 pallet KLT4013	(BT63447)	=	40	pcs. (incl. lids D41 - BT63448)
1 pallet KLT4213	(BT59936)	=	40	pcs. (incl. lids D45 - BT60297)
1 pallet KLT6013	(BT63449)	=	20	pcs. (incl. lids D61 - BT63450)
1 pallet KLT6147	(BT62593)	=	28	pcs. (incl. lids D65 - BT62539)
1 pallet KLT8420	(BT57600)	=	15	pcs.
1 pallet A1208	(BT00233)	=	25	pcs.
1 pallet MU 3	(BT05815)	=	27	pcs.
1 pallet MU 4	(BT00380)	=	40	pcs.
1 pallet MU 5	(BT00013)	=	52	pcs.
1 pallet MU 5 L	(BT03073)	=	52	pcs.
1 pallet MU 6	(BT00379)	=	104	pcs.
1 pallet MU 6 L	(BT05138)	=	104	pcs.
1 pallet MU 7	(BT06501)	=	160	pcs.

4.2. Cleanliness

It is to be assumed that containers are circulated throughout the MAHLE Behr Group under industrial conditions. This includes the handling of the containers as well as a minor soiling by process-related activities on the parts which cannot be avoided.

RP shall be provided in usable condition.

RP are inspected and sorted in MAHLE Behr plants with defined quality criteria.

Container in re-usable condition must be sent to MAHLE Behr's Logistic Centers directly.

Containers to be cleaned must be sent to cleaning stations before returning them into KLT-Pool loop.

Clean / re-usable RP must be stored dryly (under roof) in any case.

Additional requirements in regards of cleanliness of RP must be defined and ensured separately.

4.3. Labeling (according VDA4902, VDA4994)

For the identification of KLT/MULTIPACK, **only non-self-adhesive** shipping/part identification labels must be used. They must have a grammage of 120g/m² at minimum.

Labels must be put into the provided label holder (KLT). Fixation with adhesive dots is not permitted.

The fixation of the labels at MULTIPACK must be done with max. 2 adhesive dots.

For identification of the handling unit, a master label must be used. The fixation must be done with max. 2 adhesive dots.

These adhesive dots can be purchased directly from the manufacturer at MAHLE Behr conditions.

Following types are available:

Adhesive dot 45 x 19 mm (item number BT56855)

Adhesive dot 30 x 30 mm (item number BT56856)

Adhesive dots may also be purchased at other manufacturers. The dots must comply with the specifications of MAHLE Behr adhesive dots.

Specifications and supplier information could be requested at KLT-Pool Management.

No other types of fixation are permitted.

4.3.1. System conform labeling:

- Non-self-adhesive label, put into label holder at KLT and 1 master label at front end fixed with max. 2 adhesive dots of defined types



- Non-self-adhesive label, fixed with max. 2 adhesive dots at MULTIPACK and 1 master label at front end fixed with max. 2 adhesive dots of defined types



- Exception MU7 – due to sizes, label must be put on long side



- Basically, size of labels (VDA 4902, VDA4994) should be aligned to size of KLT

4.3.2. System non-conform labeling:

- Label on the lid
- Label on the side
- Affixing (self-adhesive) pockets to the container
- Use of any type of tape (also Scotch tape)
- Multiple labels applied by suppliers
- Use of self-adhesive labels
- Labels between the reinforcing ribs
- Labels on the inside of the container



- To prevent parts from getting mixed up in the production process, only the currently valid shipping/parts identification label must be used on the container.

4.4. Palletizing

According to this standard Euro pallets (1200 x 800 x 144 mm) must be used for shipping of RP. MAHLE Behr part number is 804562.

4.5. Load securing

- For the delivery of full KLT/MULTIPACK, only plastic straps are permitted. When using handling unit lid A1208, the plastic strap must be routed through the grooves.



- For MULTIPACK, the plastic strap must be routed through the grooves in the lid (not the hinge).



- Exception: for MU7 plastic straps must be routed in the middle row of handling unit in addition.



4.6. Goods receipt inspection process

Inbound deliveries / packaging will be inspected at goods receipt and if non-compliant, a claim will follow. Costs will be charged to the supplier.

Following items will be checked amongst others:

- Cleanliness
- Labeling
- Palletizing
- Load securing

4.7. Area of application for RP

In principle, the RP is suitable for all parts satisfying the dimensional requirements. If using additional inserts, it is also possible to securely pack sensitive parts as well. If filled containers are handled manually, care must be taken to ensure compliance with the ergonomic and legal guidelines.

Exceptions to this rule must be defined!

4.8. Ergonomics

Weight restrictions (payload / superimposed load) must be observed for all RP.

A maximum total weight of 12 KG including packaging must not be exceeded for small boxes employed for shipments to/from MAHLE Behr, in case of manual handling.

Exception: For MU7 – BT06501 a maximum permitted total weight of 8 kg applies.

The stacking height of filled containers per pallet must be agreed with MAHLE Behr.

5. Contact person for logistic/technical standards

The department responsible for the contact/coordinating function relating to logistic and technical contents of this guideline is Corporate Logistics, Transport-/ Container Management

Mr. Jochen Rothfuß, CITE
jochen.rothfuss@mahle.com